



7810 Transconductance Amplifier

Ultra Accurate, Wideband AC Transconductance Amplifier



7810 FEATURES

- ◆ 50 A and 100 A Models!
- ◆ Wide Frequency Range (DC to 1 MHz)!
- ◆ High 9 V Voltage Compliance!
- ◆ Based on Widely Fielded 7620 and New Patented AC Current Source PCB!
- ◆ Unique Touch Screen Interface and Embedded Windows Computer!
- ◆ IEEE-488.2 and USB Interface Standards!
- ◆ SCPI Based Programming!
- ◆ Excellent Short Term Stability!
- ◆ Distortion Below -60 dB!
- ◆ Stable with Inductive Loads!
- ◆ High Output Impedance!

Guildline Instruments 7810 Wideband Transconductance Amplifier is the latest innovation for High Current, Wide Bandwidth AC Outputs. The 7810 operates from DC to 1 MHz with very low distortion. By connecting the output from a stable voltage source, the 7810 is capable of producing outputs up to 100 A over a specified frequency range of DC to 1 MHz.

With a touch sensitive screen, the 7810 provides the capability of calibrating any device requiring a known stable source of AC current up to 100 A, manually or via automation. The Transconductance Amplifier satisfies AC current measurement requirements at power and frequencies up to 1 MHz.

The 7810 provides up to 100 Amperes output. This is based on a Guildline designed, and patent protected, AC source. The output of the 7810 is based on a unique patented multi cell current source array developed at Guildline Instruments. This output array is extremely stable, with a zero drift of less than 50 ppm/hour at 100 Amperes at 100 kHz. The 7810 also offers an impressive 7 to 9 V output compliance voltage.

GUILDLINE'S NEW 7810 TRANSCONDUCTANCE AMPLIFIER PROVIDES THE LATEST IN NEW PATENTED TECHNOLOGY AND INNOVATION - WHILE ACHIEVING INDUSTRY LEADING MEASUREMENT!

To automate testing and calibration setups, the 7810 Series is controllable via the IEEE-488.2 bus interface, or USB interface. Additionally, full manual operation is achieved via the embedded Windows Based Computer. The 7810 has a touch sensitive screen and display capable of providing input control, output control, overload indication and temporary storage of data from manual operation.

Uses for the Amplifier include calibration of alternating current (AC) and direct current (DC) shunts and resistors up to 100 A and 1 MHz; and calibration of AC and DC ranges on analogue and digital multimeters.

7810 Wideband Transconductance Amplifier

Accuracy (12 Months) ± (% of Reading + % of Range) 1 Hour Warm-up

Selected Range ⇌	100 A	50 A	5A
Output Currents ⇌	50 A to 100 A	5 A to 50 A	0.5 A to 5 A
DC	± (0.02 + 0.015)	± (0.02 + 0.015)	± (0.02 + 0.015)
10 Hz – 10 kHz	± (0.05 + 0.04)	± (0.05 + 0.04)	± (0.05 + 0.04)
10 kHz – 20 kHz	± (0.10 + 0.08)	± (0.10 + 0.08)	± (0.10 + 0.08)
20 kHz – 50 kHz	± (0.15 + 0.12)	± (0.15 + 0.12)	± (0.15 + 0.12)
50 kHz – 100 kHz	± (0.30 + 0.24)	± (0.30 + 0.24)	± (0.30 + 0.24)
100 kHz – 1 MHz	TBD	TBD	± (1.00 + 0.5)

Accuracy (12 Months) ± (% of Reading + % of Range) 1 Hour Warm-up

Selected Range ⇌	500 mA	50 mA	5 mA
Output Currents ⇌	5 mA to 500 mA	5 mA to 50 mA	0.5 mA to 5 mA
DC	± (0.02 + 0.015)	± (0.02 + 0.015)	± (0.02 + 0.015)
10 Hz – 10 kHz	± (0.05 + 0.04)	± (0.05 + 0.04)	± (0.05 + 0.04)
10 kHz – 20 kHz	± (0.10 + 0.08)	± (0.10 + 0.08)	± (0.10 + 0.08)
20 kHz – 50 kHz	± (0.15 + 0.12)	± (0.15 + 0.12)	± (0.15 + 0.12)
50 kHz – 100 kHz	± (0.30 + 0.24)	± (0.30 + 0.24)	± (0.30 + 0.24)
100 kHz – 1 MHz	± (1.00 + 0.5)	± (1.00 + 0.5)	± (1.00 + 0.5)

GENERAL SPECIFICATIONS

10 Minute Stability ▶	Frequency	± % of Reading + % of Range
	DC	0.002 + 0.002
	10 Hz to 10 kHz	0.005 + 0.005
	10 kHz to 100 kHz	0.01 + 0.01
Harmonic Distortion ▶	100 kHz to 1 MHz (up to 5 A)	0.05 + 0.05
	10 Hz to 10 kHz	-60 dB
	10 kHz to 40 kHz	-50 dB
	40 kHz to 100 kHz	-40 dB
Inductive Load Stability ▶	100 kHz to 1 MHz (up to 5 A)	-30 dB
	Free of oscillations with inductive loads up to 1 mH	
Compliance Voltage ▶	Maximum 9 Vdc or 9 Vrms (± 0.1 V) Up to 5 A	
	Maximum 7 Vdc or 7 Vrms (± 0.1 V) 5 A to 100 A	
Noise ▶	± 0.05 % of current range in a band from DC to 100 kHz	
Power Factor Correction ▶	Power factor corrected with a nominal power factor rating of 0.98	
Frequency Uncertainty ▶	0.01 % of reading over a range of 10 Hz to 100 kHz	
	0.05 % of reading over a range of 100 kHz to 1 MHz	

7810 Wideband Transconductance Amplifier

GENERAL SPECIFICATIONS (CONTINUED)

Output Offset ▶	Less than ± 3 ppm of full scale for each range		
Input Impedance ▶	≥ 500 kΩ		
Communications ▶	IEEE 488.2 / USB	SCPI Based Instructions	
Output Connectors ▶	25 - 100 A (LC)	<25 A (Type N)	
Dimensions (H x D x W) All Models ▶	17" x 22" x 17.5"	43.2 cm x 55.9 cm x 44.5 cm	
Operating Temperature to Full Specifications ▶	22.8 °C ± 3.3 °C	73 °F ± 6 °F	
Maximum Operating Range (<80 % RH) ▶	+18 °C to +28 °C	+64.4 °F to +82.4 °F	
Temperature Storage Range ▶	-20 °C to +60 °C	-4 °F to +140 °F	
Operating Humidity	20 % to 50 % RH	Storage Humidity	15 % to 80 % RH
Power (Note 220/240 Single Phase) ▶	110, 115, 120, 220, 240 VAC ± 10 %	50 Hz or 60 Hz ± 5 %	

Unparalleled Support

Guildline Instruments provides an industry leading two-year warranty on every 7810 Wideband Transconductance Amplifier. We know that the 7810 will work for you out of the box!

AC Shunts - Our 7340 and 7350 Series of AC/DC Shunts are available in a variety of ohmic and current values and provide the lowest uncertainties found in any commercial AC/DC Shunt. Housed in a ruggedized EMI case, these models provide a wide frequency bandwidth of up to 100 kHz and with currents to 100 A for the 7340 Series and 25 A for the 7350 Series. Adaptors and cable sets are also available for these models.



APPLICABLE DOCUMENTS

This Transconductance Amplifier is designed for safety and meets the requirements of the following documents:

International Electro-Technical Commission Standards

- IEC 61326 Electromagnetic Compatibility, Electrical Equipment for Measurement & Laboratory Use
- IEC 61010-1 Safety Requirements for Electrical Equipment for Measurement, Control and Laboratory Use PART 1: General Requirements

IEEE Standards

- ANSI/IEEE Std. 488.2-1992 Standard Codes, Formats, Protocols and Common Commands for use with ANSI/IEEE Std 488.1-1987
- USB-2.0 Universal Serial Bus Specification

ORDERING INFORMATION

7810	Wideband Transconductance Amplifier
/RC	Report of Calibration Available at Additional Charge
/TM7810	Technical Manual included
Accessories Available - Contact Guildline	

GUILDLINE IS DISTRIBUTED BY:

Guildline Instruments Limited
 21 Gilroy Street, PO Box 99
 Smiths Falls, Ontario
 Canada, K7A 4S9
 Phone: (613) 283-3000
 Fax: (613) 283-6082
 Web: www.guildline.com
 Email: sales@guildline.com